

N-Channel Enhancement Mode MOSFET

Feature

- 40V/334A
 $R_{DS(ON)} = 0.95 \text{ m}\Omega(\text{typ.}) @ V_{GS} = 10\text{V}$
- 100% Avalanche Tested
- 100% DVDS
- Reliable and Rugged
- Halogen Free and Green Devices Available
(RoHS Compliant)

Applications


- Load Switch
- DC-DC
- Lithium battery protect board

Pin Description



Pin 1

TOLL



Pin 2,3,4,5,6,7,8

Single N-Channel MOSFET

Ordering and Marking Information

 TA HYG011N04 XYMXXXXXX	Package Code TA: TOLL Date Code XYMXXXXXX
---	---

Note: HUAYI halogen free products contain molding compounds and 100% matte tin plate Termination finish; which are fully compliant with RoHS. HUAYI halogen free products meet or exceed the halogen free requirements of IPC/JEDEC J-STD-020 for MSL classification at halogen free peak reflow temperature. HUAYI defines "Green" to mean halogen free (RoHS compliant) and halogen free (Br or Cl does not exceed 900ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500ppm by weight).

HUAYI reserves the right to make changes, corrections, enhancements, modifications, and improvements to this product and/or to this document at any time without notice.

Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (Tc=25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		40	V
V _{GSS}	Gate-Source Voltage		± 20	V
T _J	Junction Temperature Range		-55 to 175	°C
T _{STG}	Storage Temperature Range			°C
I _S	Source Current-Continuous(Body Diode)	Tc=25°C	334	A
Mounted on Large Heat Sink				
I _{DM}	Pulsed Drain Current *	Tc=25°C	1330	A
I _D	Continuous Drain Current	Tc=25°C	334	A
		Tc=100°C	236	A
P _D	Maximum Power Dissipation	Tc=25°C	241	W
		Tc=100°C	120	W
R _{θJC}	Thermal Resistance, Junction-to-Case		0.62	°C/W
R _{θJA}	Thermal Resistance, Junction-to-Ambient **		45	°C/W
E _{AS}	Single Pulsed-Avalanche Energy ***	L=0.3mH	776	mJ

Note: * Repetitive rating; pulse width limited by max.junction temperature.

** Surface mounted on 1in2 FR-4 board.

*** Limited by T_{Jmax}, starting T_J=25°C, L = 0.3mH, R_G= 25Ω, V_{GS}=10V.

Electrical Characteristics(Tc =25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	HYG011N04NS1			Unit
			Min	Typ.	Max	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V,I _{DS} =250μA	40	-	-	V
I _{DSS}	Drain-to-Source Leakage Current	V _{DS} =40V,V _{GS} =0V	-	-	1	μA
		T _J =125°C	-	-	50	μA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	2	3	4	V
I _{GSS}	Gate-Source Leakage Current	V _{GS} =± 20V,V _{DS} =0V	-	-	±100	nA
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =10V,I _{DS} =40A	-	0.95	1.2	mΩ
Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _{SD} =40A,V _{GS} =0V	-	0.79	1.20	V
t _{rr}	Reverse Recovery Time	I _{SD} =40A,dI _{SD} /dt=100A/μs	-	47	-	ns
Q _{rr}	Reverse Recovery Charge		-	49	-	nC

Electrical Characteristics (Cont.) (Tc =25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	HYG011N04NS1			Unit
			Min	Typ.	Max	
Dynamic Characteristics						
R _G	Gate Resistance	V _{GS} =0V,V _{DS} =0V,f=500kHz	-	1.6	-	Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =25V, f=500kHz	-	5816	-	pF
C _{oss}	Output Capacitance		-	1312	-	
C _{rss}	Reverse Transfer Capacitance		-	57	-	
t _{d(ON)}	Turn-on Delay Time	V _{DD} =20V,R _G =4Ω, I _{DS} =40A,V _{GS} =10V	-	25	-	ns
T _r	Turn-on Rise Time		-	75	-	
t _{d(OFF)}	Turn-off Delay Time		-	56	-	
T _f	Turn-off Fall Time		-	57	-	
Gate Charge Characteristics						
Q _g	Total Gate Charge(V _{GS} =10V)	V _{DS} =32V, I _{DS} =20A	-	85	-	nC
Q _{gs}	Gate-Source Charge		-	28	-	
Q _{gd}	Gate-Drain Charge		-	13	-	
V _{plateau}	Gate plateau voltage		-	4.6	-	V

Note: *Pulse test, pulse width ≤ 300us, duty cycle ≤ 2%

Typical Operating Characteristics

Figure 1: Power Dissipation




Figure 2: Drain Current




Figure 3: Safe Operation Area




Figure 4: Thermal Transient Impedance




Figure 5: Output Characteristics





Figure 6: Drain-Source On Resistance



Typical Operating Characteristics(Cont.)

Figure 7: On-Resistance vs. Temperature




Figure 8: Source-Drain Diode Forward




Figure 9: Capacitance Characteristics







Figure 10: Gate Charge Characteristics





Avalanche Test Circuit





$$E_{AS} = \frac{1}{2} L I_{AS}^2$$



Switching Time Test Circuit



Gate Charge Test Circuit



Package Information

Package Type	Unit	Quantity
TOLL	Reel	2000

Package Information

Technical drawing of the 1000 series 1000V 100A molded case circuit breaker (MCCB) showing front, side, and top views with dimensions in mm.

Front View Dimensions:

- Overall width: 10.38 ± 0.2 [D]
- Top flange width: 3.3 ± 0.15 [D2]
- Bottom flange width: 0.6 ± 0.12 [L2]
- Terminal block width: 9.9 ± 0.2 [E]
- Terminal pitch (2~7): $(2 \sim 7 \text{ 引脚}) 6 \times 0.70^{+0.1}_0$ [b]
- Terminal pitch (1~2, 7~8): $(1 \sim 2, 7 \sim 8 \text{ 引脚间距}) 2 \times 1.225 \pm 0.05$ [e]
- Top flange thickness: 0.7 ± 0.2 [L1]
- Terminal block height: 4.55 ± 0.15 [Q1]


Side View Dimensions:

- Overall height: 2.3 ± 0.15 [A]
- Bottom flange thickness: $0.5^{+0.1}_{-0.05}$ [C]

Top View Dimensions:

- Overall width: 9.8 ± 0.15 [b1]
- Terminal block width: 8.1 ± 0.15 [E1]
- Terminal pitch (2~7): $(2 \sim 7 \text{ 引脚间距}) 5 \times 1.2 \pm 0.05$ [e']
- Terminal pitch (1~2, 7~8): $(1 \sim 2, 7 \sim 8 \text{ 引脚间距}) 2 \times 1.225 \pm 0.05$ [e]
- Terminal block height: 6.95 ± 0.15 [H1]
- Overall height: 11.68 ± 0.2 [H]
- Terminal block thickness: 1.8 ± 0.2 [L]
- Terminal block width: 1.15 ± 0.15 [L4]

Classification Profile



Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak		
Temperature min (T_{smin})	100 °C	150 °C
Temperature max (T_{smax})	150 °C	200 °C
Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds	60-120 seconds
Average ramp-up rate (T_{smax} to T_P)	3 °C/second max.	3°C/second max.
Liquidous temperature (T_L)	183 °C	217 °C
Time at liquidous (t_L)	60-150 seconds	60-150 seconds
Peak package body Temperature (T_P)*	See Classification Temp in table 1	See Classification Temp in table 2
Time (t_p)** within 5°C of the specified classification temperature (T_C)	20** seconds	30** seconds
Average ramp-down rate (T_P to T_{smax})	6 °C/second max.	6 °C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.
*Tolerance for peak profile Temperature (T_P) is defined as a supplier minimum and a user maximum.		
** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.		

Table 1.SnPb Eutectic Process – Classification Temperatures (Tc)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2.Pb-free Process – Classification Temperatures (Tc)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ ≥2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 mm – 2.5 mm	260 °C	250 °C	245 °C
≥2.5 mm	250 °C	245 °C	245 °C

Reliability Test Program

Test item	Method	Description
SOLDERABILITY	JESD-22, B102	5 Sec, 245°C
HTRB	JESD-22, A108	168/500/1000 Hrs, Bias @ 150°C
HTGB	JESD-22, A108	168 /500/1000Hrs, V _{gs} 100% @ 150°C
PCT	JESD-22, A102	96 Hrs, 100%RH, 2atm, 121°C
TCT	JESD-22, A104	250/500/1000 Cycles, -55°C~150°C

Customer Service

Worldwide Sales and Service: sales@hymexa.com

Technical Support:Technology@hymexa.com

Huayi Microelectronics Co., Ltd.

No.8928,Shangji Road,Economic and Technological Development Zone,Xi'an,China

TEL: (86-029) 86685706

FAX: (86-029) 86685705

E-mail: sales@hymexa.com

Web net: <http://www.hymexa.com/>